



Industrial filtration

Betafine PBG filter cartridges

Pleated polypropylene graded-porosity filter cartridges

Filters for food and beverage applications

The Thermo Scientific™ Betafine™ PBG Filter Cartridge represents a major advance in pleated filter technology and performance. This absolute-rated, graded-porosity 100% polypropylene pleated filter cartridge features Advanced Pleat Technology (APT) that increases the usable filtration surface area while maintaining standard industrial cartridge dimensions. The result is a filter cartridge that dramatically enhances service life.



Features and benefits

Features	Benefits
Advanced Pleat Technology (APT) construction for high surface area as compared to competitive filters	• Higher product throughputs for prolonged service life • Lower total filtration operating costs • Lower pressure drops for higher flow rates
Absolute-rated filter performance	• Higher product quality and yields
Graded-porosity multi-layer filter media	• Capture of contaminant throughout the filter media to help maximize filter life • Higher contaminant holding capacity
Backflushable, polypropylene cartridge components	• Very low extractable levels for optimum filtrate purity • Broad compatibility with solvents and cleaning solutions

Applications

Betafine PBG filter cartridges are ideal for a wide array of prefiltration and clarification applications where reliability and economy are critical. Suggested applications include:

Food and beverage service

- Protection and longevity of membrane final filters
- Final particle control
- Food fermentation feeds, intermediates and fermentation clarification
- Blending water filtration
- Cleaning fluids
- Solvent streams, air and gas prefiltration and final filtration


Betafine PBG filter cartridges for food and beverage service

Certain Betafine PBG filter cartridges are compliant with US FDA 21 CFR, EU Food Contact Regulation (EC) 1935/2004, EU Food Contact Regulation 10/2011, and other food contact regulations. Contact your Thermo Fisher Scientific Inc. representative for detailed declaration of compliance information for food contact applications. The filter cartridge can be autoclaved, steamed-in-place (in situ), and sanitized with hot water. The durable polypropylene construction provides excellent performance in all food and beverage filtration applications.


- Backflushable — Betafine PBG filter cartridge applications can be designed with a variety of methods to extend service life. Combined with hot water sanitation or other in-line cleaning procedures, backflushing Betafine PBG filter cartridge systems can extend service life significantly.

Protection of final membranes

Beverage bottlers frequently employ membrane filter cartridges to achieve microstability without heat pasteurization. Typical retention ratings for the final filter are 0.45 µm or 0.65 µm. The Betafine PBG filter cartridge's absolute retention, graded-porosity structure and large surface area are ideal for prefiltration protection of final sterilizing membranes. By removing contaminants before the final filter, the service life of expensive membrane filter cartridges are extended significantly.



Graph 1. Clean water flow per 10-inch Thermo Scientific™ Betafine™ PBG Filter Cartridge at ambient temperature 68°F (20°C)



Operating parameters and specifications

Material of construction		
Filter media	Graded-porosity pleated polypropylene	
Media support layers	Polypropylene	
Inner core, outer cage, end cap adapters	Polypropylene	
Gasket and O-ring options	Silicone, FEP/PFA, TES	
Adapter support ring	Stainless steel	
Filter cartridge dimensions		
Filtration surface area	060, 100, 120, 250	8.8 ft² (0.82 m²)
Filtration surface area	020	8.1 ft² (0.75 m²)
Filtration surface area	500	8.6 ft² (0.8 m²)
Outside diameter	2.8 in (71 mm)	
Nominal length	10 in (254 mm), 20 in (508 mm), 30 in (762 mm)	
Operating parameters		Specification
Maximum operating temperature	140°F (60°C), 176°F (80°C)	
Maximum differential pressure (forward and reverse)	60 psid (4.1 bar) @ 77°F (25°C)	


Ordering guide

Betafine PBG filter cartridges ordering guide

Cartridge type	Grade code and rating (µm)	Configuration	Length (inches)	End modification	Gasket material/O-ring	Reinforcing ring
PBG	020 - 0.20 060 - 0.60 120 - 1.2 250 - 2.5 500 - 5.0	B	01 / 10 in 02 / 20 in 03 / 30 in	B - 226 O-ring & spear C - 222 O-ring & spear F - 222 O-ring & flat cap	A - Silicone K - TEV - Encapsulated PTFE X - FEP/PFA - Encapsulated silicone	Stainless steel
				D - Double open end (DOE)	A - Silicone	N/A

¹ Retention ratings determined by Thermo Fisher test method TP. The 0.2 µm rating has been extrapolated. For more information, contact your Thermo Fisher Scientific representative.

Please note: The order guide above is for reference only.
 Not all combinations are available. Please consult with your Thermo Fisher Scientific representative to determine the appropriate part number for your application.



Intended Use: Betafine PBG filter cartridge products are intended and are compliant for use in Food and Beverage filtration applications of aqueous and non-aqueous fluids in accordance with the product instructions, specifications and where materials of construction are compatible. For specific details regarding use or limitations for food contact applications please contact your Thermo Fisher Scientific Inc. representative for more information.

Since there are many factors that can affect a product's use, the customer and user remain responsible for determining whether the Thermo Scientific product is suitable and appropriate for the user's specific application, including user risk assessment and evaluation of the Thermo Scientific product in the user's application.

Restrictions on Use: Thermo Fisher Scientific Inc. advises against the use of these Thermo Scientific products in any application other than the stated intended use(s) since other applications have not been evaluated by Thermo Fisher and may result in an unsafe or unintended condition. Do not use in any manner whereby the Thermo Scientific product, or any extractable or leachable from the Thermo Scientific product, may become part of or remain in a medical device, drug, cosmetic, supplement, infant formula; or in applications involving life-sustaining medical applications or prolonged contact with internal bodily fluids or tissues.

Technical Information: The technical information, guidance, and other statements contained in this document or otherwise provided by Thermo Fisher are based upon records, tests, or experience that Thermo Fisher believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with sufficient knowledge and technical skills to assess and apply their own informed judgment to the information. No license under any Thermo Fisher or third-party intellectual property rights is granted or implied with this information.

Product Selection and Use: Many factors beyond Thermo Fisher's control and uniquely within user's knowledge and control can affect the use and performance of a Thermo Scientific product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application. Failure to properly evaluate, select, and use a Thermo Scientific product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.



Autorised distributor of Thermo Scientific™ products in Italy
www.vason.com

For more information contact your Thermo Fisher Scientific sales representative or visit thermofisher.com/industrialfiltration

thermo scientific